



BS62-4A/28

4-stroke Rammers

Outstanding work performance and long service life

Wacker Neuson's 4 stroke rammers characterized by excellent work performance. The long shoe stroke, the high ramming frequency, high impact energy and fast travel speed ensure firstclass work results. Well thought-out functions make the use of the 4 stroke rammers even more operator-friendly, extend their service life, and minimize maintenance.

Highlights

- Large stroke, high impact force
- Just one lever for starting, idling and stopping
- Efficient air filter
- Ergonomic guide handle
- Low oil warning indicator
- Large stroke, high impact force
- Efficient air filter
- Ergonomic guide handle

Technical Data

Mechanical - Output Details		stroke at tamper	68.0 mm
Number of blows	689.0 1/min	Environment Data	
Area capacity	202.0 m2/h	Operating temperature range	-10 - 40 °C
Forward running	12.0 m/min	Sound power LWA, guaranteed	108.0 dB(A)
Power of impact	17.0 kN	Sound power LWA (Standard)	EN 500-4
Mechanical Details		HAV summation (average value)	10.0 m/s2
Length	662.0 mm	HAV summation (Standard)	EN 500-4
Length Ramming Shoe	340.0 mm	Electrical System	
Width	347.0 mm	Operating elements	Pushbutton OFF
Width Ramming Shoe	280.0 mm	Operating Fluids	
Height	920.0 mm	Oil specification	SAE 10W-40
Weight	63.20 kg	Oil volume	0.700 l
Operating weight	64.0 kg		

The illustrations, equipment and data shown may deviate from the current delivery program of your country. Optional equipment subject to additional charge may be shown. Subject to changes.