



## **BS68-4A/28**

### 4-stroke Rammers

# Outstanding work performance and long service life

Wacker Neuson's 4 stroke rammers characterized by excellent work performance. The long shoe stroke, the high ramming frequency, high impact energy and fast travel speed ensure firstclass work results. Well thought-out functions make the use of the 4 stroke rammers even more operator-friendly, extend their service life, and minimize maintenance.

### Highlights

- Large stroke, high impact force
- Just one lever for starting, idling and stopping
- Efficient air filter
- Ergonomic guide handle
- Low oil warning indicator
- Large stroke, high impact force
- Efficient air filter
- Ergonomic guide handle

#### **Technical Data**

| Mechanical - Output Details |             | stroke at tamper              | 63.0 mm        |
|-----------------------------|-------------|-------------------------------|----------------|
| Number of blows             | 689.0 1/min | Environment Data              |                |
| Area capacity               | 202.0 m2/h  | Operating temperature range   | -10 - 40 °C    |
| Forward running             | 12.0 m/min  | Sound power LWA, guaranteed   | 108.0 dB(A)    |
| Power of impact             | 19.0 kN     | Sound power LWA (Standard)    | EN 500-4       |
| Mechanical Details          |             | HAV summation (average value) | 9.4 m/s2       |
| Length                      | 662.0 mm    | HAV summation (Standard)      | EN 500-4       |
| Length Ramming Shoe         | 340.0 mm    | Electrical System             |                |
| Width                       | 347.0 mm    | Operating elements            | Pushbutton OFF |
| Width Ramming Shoe          | 280.0 mm    | Operating Fluids              |                |
| Height                      | 950.0 mm    | Oil specification             | SAE 10W-40     |
| Weight                      | 69.10 kg    | Oil volume                    | 0.900          |
| Operating weight            | 70.0 kg     |                               |                |

The illustrations, equipment and data shown may deviate from the current delivery program of your country. Optional equipment subject to additional charge may be shown. Subject to changes.